



ISUM FAST ACRYLIC



DESCRIPTION:

Special lightweight filler/sealant based on acrylic water dispersion.

APPLICATIONS:

ISUM FAST ACRYLIC is specially designed for repairing and filling cracks, holes, fissures, etc. in plaster or cement walls, and in general any kind of porous construction material.

It is also suitable for sealing joints without or with low movement in plasterboard or drywall systems.

PROPERTIES:

ISUM FAST ACRYLIC is a lightweight filler easy to apply thanks to its good extrusion properties. It dries quickly, does not shrink, nor crack once dry.

It can be used indoor and outdoor.

INSTRUCTIONS:

Surfaces to be filled must be clean and free of any dust and grease.

Apply **ISUM FAST ACRYLIC** directly with the nozzle of the cartridge. Smooth the surface with a moistened spatula to obtain a good smooth finish.

Once the product is dry it can be sanded or painted if necessary.

TECHNICAL FEATURES:

Form: White paste.

Viscosity: Paste of thixotropic consistency.

Density at 23°C: $0,450 \pm 0,050 \text{ gr/cm}^3$

PRESENTATION:

Cartridge 300 ml

STORAGE:

Store up to 12 months in its original closed container at temperatures between 5 and 30°C.

Protect from frost.

CLEANING:

The cleaning of tools can be made with warm water.

HEALTH & SAFETY:

According to the current legislation, this product is exempt of any indication of risk or security in its handling or storage.

For more information request the Safety Data Sheet.

"The information contained herein is offered in good faith based on producer research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that producer products are fully satisfactory for your specific applications. Producer sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Producer specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Producer disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.

Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically."



ISUM Agnieszka Mikulska
ul. Jaśminowa 28, 87-100 Toruń
PL9522133762 tel. +48720797529 biuro@isum.pl